

JLS560B	24	10	B	BB	N/A	DD
Model	Voltage	Width	CCT	IP	CRI	Length
	24: 24V	10: 10mm	Blue	33: IP33 (Dry) 55: IP55 (Damp) 65: Nano (Damp) 67: IP67 (Wet)	N/A	5m (SD) Customized



CCT	Power
Blue	4.39 W/ft

Project	
Qty	
Date	
Client	

Standard CCT



Blue
470nm

Waterproof Solution



IP33
No waterproof

Dry location



IP55
Silicone Coating

Damp location



IP65
Waterproof

Damp location



IP67
Silicone Extrusion

Wet location
Short time under water

LED Type	SMD5050
Input Voltage	24VDC
Beam Angle	120°
CRI	N/A
Power	B: 14.4W/m (4.39W/ft)
Length/ Reel	5m(16.4ft)/ 50m/(164ft)
Cut Length	100mm/unit (3.94in/unit)
Max. Length (No Voltage drop)	5m (16.4ft)
IP Grade	IP33/ IP55/ IP65/ IP67
Operating Temperature	-20°C~45°C
Environment Humidity	40-70% RH
Dimming Method	0-10V, RX, PWM, Triac, RF, Bluetooth, WIFI etc.
Certification	UL, CE, RoHS

DIMENSION

